



POLYISOCYANURATE 2 LB INSULATION
CURVED SIDEWALL AND FLAT BEVELLED SEGMENTS

Segmented with Butt Joints - Unjacketed

Fabricated to ASTM Recommended Practice C450-76

LIST PRICES PER SQUARE FOOT: Subject to Trade Discounts.

NOMINAL THICKNESS SINGLE LAYER		VESSEL OUTSIDE DIAMETER:						NOMINAL Thickness
		Curved Sidewall Segs				Flat & Bevelled Segs		
mm	Inches	14-71" (43-180cm)		72-144" (183-366cm)		> 144" (366cm)		Inches
		\$/Bd.Ft.	\$/Sq.Ft.	\$/Bd.Ft.	\$/Sq.Ft.	\$/Bd.Ft.	\$/Sq.Ft.	
38	1.5	12.720	19.08	12.300	18.45	10.140	15.21	1.5
51	2.0	11.670	23.34	11.550	23.10	9.540	19.08	2.0
64	2.5	10.836	27.09	10.728	26.82	9.132	22.83	2.5
76	3.0	10.320	30.96	10.230	30.69	8.900	26.70	3.0
89	3.5	10.209	35.73	10.097	35.34	8.700	30.45	3.5
102	4.0	9.870	39.48	9.803	39.21	8.580	34.32	4.0
114	4.5	9.633	43.35	9.573	43.08	8.460	38.07	4.5
127	5.0	9.624	48.12	9.546	47.73	8.388	41.94	5.0

SEGMENT DIMENSION	VESSEL O.D.	Nominal Chord Width unless otherwise requested	Length
Curved Sidewall	14" TO 35"	8"	36"
Curved Sidewall	36" TO 71"	12"	36"
Curved Sidewall	72" TO 120"	12"	36"
Curved Sidewall	121" TO 144" +	24"	36"
Flat & Bevelled	> 144"	to advise	36"

All fabrication is completed according to applicable industry standards.

Traced items are cut to the next smaller Nominal pipe size and larger thickness, i.e. NPS 3 1/2" x 1 1/2" is cut to a 3" x 2" specification. Please advise if alternative fabrication is required.

Elbows, pipe cover and segments are packaged in corrugated cardboard cartons or clear UV resistant plastic bags.

To determine the extent of sizing for any material, please provide our customer service staff with a list of sizes and quantities.

Our sales policy is applicable. Fabricated items are non-returnable. Some sizes are special order and all pricing is provided for information purposes only. Prices & specifications are subject to change without notice and feel free to contact our office with any questions.

G.S.T. Extra @ 5%.