

FASTENERS



Amity Insulation is proud to offer a variety of accessories for your insulating and jacketing needs.

STRAPPING/BANDING

Amity Stainless Steel Strapping/Banding is manufactured from Type 304 stainless steel. The edges are deburred for safe handling and the banding is available in $\frac{1}{2}$ " x .015 and .020 and $\frac{3}{4}$ " x .020 thicknesses. All are available in ribbon and oscillated wound coils or as pre-made fabricated straps with wing seals.



SEALS

Amity Wing Seals are available in Stainless Steel to match the width of strapping being used. Seals are fabricated in-house and are available in $\frac{1}{2}$ " and $\frac{3}{4}$ " widths with .024 and .032 respective thicknesses. Stainless Steel Closed Seals are also available for special applications.

STAINLESS STEEL SHEET METAL SCREWS

Amity Stainless Steel Screws are manufactured from T304 Stainless Steel to provide fastening for all types of sheet metal jacketing and duct work, and include:

- #8 x $\frac{1}{2}$ " stainless steel pan head Robertson (square socket) self tapping sheet metal screws;
- #8 x $\frac{1}{2}$ " stainless steel hex head Robertson (square socket) self tapping sheet metal screws;
- #8 x $\frac{1}{2}$ " galvanized/zinc plated hex head Robertson (square socket) self-tapping sheet metal screws, and many more.

END-CAPPING, WIRE, AND SEALANT

End-capping is manufactured in coils of aluminum strip which is bent and shaped to cover the exposed ends of insulated pipe. A wide range of widths are available to suit most common insulation thicknesses. The end-capping provides a neat finish to the end of pipes and is available in polished aluminum.

The Stainless Steel wire is type 304 soft annealed, and is available in 16 and 18 gauge thicknesses. Aluminum Sealant is supplied in many form from top manufacturers such as Dow Corning and GE.



This information is representative at the time of publication and should not be deemed to constitute or imply any warranty of performance. The user is responsible for determining the suitability of the material for the respective application. All drawings, descriptions and photos remain Amity's exclusive property and cannot be used without the prior written consent of Amity management. This publication renders all previous copies invalid. Amity's sales policy is applicable at all times. PROtherm is a registered trademark.