

STAINLESS STEEL BANDING DISPENSER



CHARACTERISTICS

Amity Insulation specializes in the supply of high performance banding for all applications. Stainless steel metal banding is used as a fastening system in insulation, construction and also the sign industry.

Amity is proud to offer an easy to use dispenser as part of its product line. Amity Banding is manufactured within the scope of ISO 9001:2015 management system.

Banding can be supplied in a simple to use plastic dispenser as displayed which can be accessible and easy to access in any contractor vehicle.

PHYSICAL ATTRIBUTES

Austenitic Stainless Steel	ASTM A240/EN 10088-2
Grade:	Stainless Steel Type 304 BA
Tolerance:	Thickness +/- 0.004" and Width +/- 0.04".
Coil Weight:	Approximately 6 lbs.
Width:	1/2"
Thickness:	0.020"
Coil ID: 4"	Coil OD: "8"

Coil with different specifications may be available upon request. All coils are in approximately 160 lineal foot rolls and come with 100 wing seals (1/2") for quick fastening requirements.

We are committed to offering superior service to accompany the high quality ISO certified materials that we supply. Please contact your sales representative at Amity Insulation Group Inc. for further information if required.

This information is representative at the time of publication and should not be deemed to constitute or imply any warranty of performance. The user is responsible for determining the suitability of the material for the respective application. All drawings, descriptions and photos remain Amity's exclusive property and cannot be used without the prior written consent of Amity management. This publication renders all previous copies invalid. Amity's sales policy is applicable at all times. PROtherm is a registered trademark.